

Congoleum®

Alternatives™

Commercial Vinyl Composition Tile

Product:	Alternatives
Construction:	Vinyl Composition (Polish required)
Gauge (nominal):	0.125" (1/8") (3.2mm)
Size:	12" X 12"
Packaging:	45 sft/carton
Shipping Weight per Package:	64 lbs/carton
Passes NBS Smoke Density:	Yes
Passes Critical Radiant Flux (ASTM E-648 > 0.45w/cm²):	Yes
Static Load Limit:	250 psi
Slip Resistance:	Meets ADA Recommendations
FloorScore Certified:	Yes
Applicable Specifications:	ASTM F1066, Cl. 2 MIL STD-1 623 D for Deck Covering
Warranty Coverage:	10 Year (Residential) 5 Year (Commercial)
Installation Method:	Fully Adhered
Subfloor Application:	On, above or below grade level
Adhesive:	Congoleum AD-42 Clear Thin-Spread
Adhesive Coverage:	
Fully adhered:	250 to 300 sq. ft. per gallon
Recommended Trowel:	1/16" wide, 1/32" deep, 1/32" apart
Suggested Usage:	
Public Commercial	Excellent
Light Commercial	Excellent
Private Residential	Good

Finished product manufactured in the United States

Congoleum®

Alternatives™

Vinyl Composition Tile 12" x 12"



AL106 Alabaster*



AL116 Stark*



AL126 White Sand



AL136 Warm Stone



AL146 Latte*



AL156 Butter



AL166 Smoky Taupe



AL176 Sable



AL186 Light Camel



AL196 Mink



AL206 Cirrus



AL216 Sage



AL226 Iceberg




AL236 Pewter*



AL246 Slate*



AL256 Starry Night



AL266 Tapenade

*Stocking Color at Select Branches